


Szerokość wieńca "h"

moduł:

- 1 = 15 mm
- 1,5 = 17 mm
- 2 = 20 mm
- 2,5 = 25 mm
- 3 = 30 mm
- 4 = 40 mm
- 5 = 50 mm
- 6 = 60 mm



Kąt przyporu (nachylenia zęba) - 20°

Mat. C45 E

Z	Mod. 1				Mod. 1,5				Mod. 2				Mod. 2,5			
	De	Dp	d	D	De	Dp	d	D	De	Dp	d	D	De	Dp	d	D
60	62	60	-	12	-	-	-	-	-	-	-	-	-	-	-	-
65	-	-	-	12	-	-	-	-	-	-	-	-	167,5	162,5	-	20
70	72	70	-	12	-	-	-	-	-	-	-	-	180,0	175,0	-	20
72	74	72	-	12	111,0	108,0	-	20	148	144	-	20	185,0	180,0	-	20
75	77	75	-	12	115,5	112,5	-	20	154	150	-	20	192,5	187,5	-	20
76	78	76	-	12	117,0	114,0	-	20	156	152	-	20	195,0	190,0	-	20
80	82	80	-	12	123,0	120,0	-	20	164	160	-	20	205,0	200,0	-	25
85	87	85	-	12	130,5	127,5	-	20	174	170	-	20	217,5	212,5	-	25
90	92	90	-	12	138,0	135,0	-	20	184	180	-	20	230,0	225,0	-	25
95	97	95	-	12	145,5	142,5	-	20	194	190	-	20	242,5	237,5	-	25
100	102	100	-	12	153,0	150,0	-	20	204	200	-	20	255,0	250,0	-	25
110	112	110	-	12	168,0	165,0	-	20	224	220	-	20	280,0	275,0	-	25
114	116	114	-	12	171,0	171,0	-	20	232	228	-	20	290,0	285,0	-	25
120	122	120	-	12	183,0	180,0	-	20	244	240	-	20	305,0	300,0	-	25
127	129	127	-	12	193,5	190,5	-	20	258	254	-	20	322,5	317,5	-	25

Z	Mod. 3				Mod. 4				Mod. 5				Mod. 6			
	De	Dp	d	D	De	Dp	d	D	De	Dp	d	D	De	Dp	d	D
30	-	-	-	-	-	-	-	-	-	-	-	-	192	180	-	25
32	-	-	-	-	-	-	-	-	170	160	-	25	204	192	-	25
35	-	-	-	-	-	-	-	-	185	175	-	25	-	-	-	-
38	-	-	-	-	160	152	-	25	200	190	-	30	240	220	-	25
40	-	-	-	-	168	160	-	25	210	200	-	30	252	240	-	25
45	-	-	-	-	188	180	-	25	235	225	-	30	-	-	-	-
48	150	144	-	25	200	192	-	25	250	240	-	30	-	-	-	-
50	156	150	-	25	208	200	-	25	260	250	-	30	-	-	-	-
52	162	156	-	25	216	208	-	25	270	260	-	30	-	-	-	-
55	171	165	-	25	228	220	-	25	285	275	-	30	-	-	-	-
57	177	171	-	25	236	228	-	25	295	285	-	30	-	-	-	-
60	186	180	-	25	248	240	-	25	310	300	-	30	-	-	-	-
65	201	195	-	25	268	260	-	25	335	325	-	30	-	-	-	-
70	216	210	-	25	288	280	-	25	360	350	-	30	-	-	-	-
72	222	216	-	25	-	-	-	-	-	-	-	-	-	-	-	-
75	231	225	-	25	308	300	-	25	385	375	-	30	-	-	-	-
76	234	228	-	25	312	304	-	25	390	380	-	30	-	-	-	-
80	240	240	-	25	328	320	-	25	410	400	-	30	-	-	-	-
85	261	255	-	25	348	340	-	25	435	425	-	30	-	-	-	-
90	276	270	-	25	368	360	-	25	460	450	-	30	-	-	-	-
95	291	285	-	25	388	380	-	25	485	475	-	30	-	-	-	-
100	306	300	-	25	408	400	-	25	510	500	-	30	-	-	-	-
110	336	330	-	25	448	440	-	25	560	550	-	30	-	-	-	-
114	348	342	-	30	464	456	-	25	580	570	-	30	-	-	-	-
120	366	360	-	30	-	-	-	-	-	-	-	-	-	-	-	-
127	387	381	-	30	-	-	-	-	-	-	-	-	-	-	-	-