



TYP	Max otwór piast		Wymiary (mm)									
	MM	INS	De	D	b	E	G	H2	B	H		
70	32	1 1/4	69	60	31	25,0	18,0	20,0	23,5	65,0	1,20	
90	42	1 5/8	85	70	32	30,5	22,5	26,0	30,0	82,5	2,15	
110	55	2 1/8	112	100	45	45,0	29,0	29,0	45,0	119,0	6,10	
130	60	2 3/8	130	105	50	53,0	36,0	36,0	55,5	147,0	8,90	
150	70	2 3/4	150	115	62	60,0	40,0	40,0	60,0	160,0	12,20	
180	80	3 1/8	180	125	77	73,0	49,0	49,0	70,0	189,0	18,40	
230	100	4"	225	155	99	85,5	59,5	59,5	90,0	239,5	35,50	
280	130	5"	275	206	119	105,5	74,5	74,5	105,5	285,5	71,50	



**Piasta sprzęgła z otworem naprowadzającym**

HRC70	0,60
HRC90	1,07
HRC110	3,05
HRC130	4,45
HRC150	6,10
HRC180	9,20
HRC230	17,75
HRC280	35,75



**Czarna wkładka**

HRC70	0,016
HRC90	0,05
HRC110	0,08
HRC130	0,15
HRC150	0,22
HRC180	0,38
HRC230	0,80
HRC280	1,53